

156-00329



Article Number: 156-00329

Description: Heavy-Duty Fir Tree Mount Cable Tie, 8" x .18", .03"-.28", Panel Thickness, PA66HIRHS, Black,500/pkg

| | | |
|-------------------------------|-----------------------|--|
| Base Data | Local Order Number | 156-00329 |
| | Type | T50RFT7HD |
| | Color | Black (BK) |
| | Features and Benefits | <ul style="list-style-type: none"> • Staggered fir tree branch design provides low insertion forces and high extraction forces. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications. |
| | Quantity Per | bag |
| | Product Description | Heavy Duty fir tree mounts with ties cables provide a secure grip in mounting holes and protect against dirt and other impurities. The mount provides low insertion and high extraction force, and slides along the cable tie for the proper orientation. This is sold as an assembly with the cable tie, and is ideal in heavy duty environments. |
| | Short Description | Heavy-Duty Fir Tree Mount Cable Tie, 8" x .18", .03"-.28", Panel Thickness, PA66HIRHS, Black,500/pkg |
| | Product Dimensions | Minimum Tensile Strength (Imperial) |
| Length L (Imperial) | | 8.0" |
| Length L (Metric) | | 200.0mm |
| Length L2 (Imperial) | | 0.5" |
| Length L3 (imperial) | | 0.78" |
| Length L3 (metric) | | 19.3mm |
| Fixation Method | | Fir Tree |
| Identification Plate Position | | none |
| Length L2 (Metric) | | 11.6mm |
| Tie Closure | | plastic pawl |
| Variant | | Inside Serrated |
| Width W (Imperial) | | 0.18" |
| Width W (Metric) | | 4.6mm |

156-00329



| | | |
|--|-------------------------------------|---|
| Product Dimensions | Width W2 (Imperial) | 0.23" |
| | Width W2 (Metric) | 5.9mm |
| | Width W3 (Imperial) | 0.23" |
| | Width W3 (Metric) | 5.9mm |
| | Height H (Imperial) | 0.78" |
| | Height H (Metric) | 19.8mm |
| | Height H2 (Imperial) | 0.36" |
| | Height H2 (Metric) | 12.4mm |
| | Bundle Diameter Min. (Imperial) | 0.16" |
| | Bundle Diameter Min. (Metric) | 4.0mm |
| | Bundle Diameter Max. (Imperial) | 1.8" |
| | Bundle Diameter Max. (Metric) | 45.0mm |
| | Disc Diameter (Imperial) | 0.9" |
| | Disc Diameter (Metric) | 21.6mm |
| | Panel Thickness Max. (Imperial) | 0.28" |
| | Panel Thickness Max. (Metric) | 7.0mm |
| | Panel Thickness Min. (Imperial) | 0.03" |
| | Panel Thickness Min. (Metric) | 0.8mm |
| | Mounting Hole Diameter D (Imperial) | 0.24 - 0.28" |
| | Mounting Hole Diameter D (Metric) | 6.3 - 7.1 mm |
| Mounting Hole Diameter D Min. (Imperial) | 0.24" | |
| Mounting Hole Diameter D Max. (Imperial) | 0.28" | |
| Material and Specifications | | |
| | Material | Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS) |
| | Material Shortcut | PA66HIRHS |
| | Flammability | UL 94 HB |
| | Operating Temperature | -40°F to +230°F (-40°C to +110°C) |
| | ROHS Compliant | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 500 |
| | Package Quantity (Metric) | 500 |
| | Customs Number(Schedule B) | 3926909987 |