

596-00587

Article Number: 596-00587

Description: Solar Label, 2017 Code, CAUTION PHOTOVOLTAIC SYSTEM BACKFED, 4.12" x .75", VL, Yellow, 50/roll



Base Data	Local Order Number	596-00587
	Type	CBACKFED
	Color	Yellow (YE)
	Features and benefits	<ul style="list-style-type: none"> • Pre-Printed Vinyl Solar Labels are made with UV-stable inks and materials for durability and weather resistance. • Supplied with an aggressive adhesive to ensure long life. • Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections. • Pre-printed labels offer significant time and cost savings over high priced plastic engraved phenolic placards and lead time purchased markers.
	Quantity Per	roll
	Product Description	HellermannTyton pre-printed vinyl Solar Installation Labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Pre-Printed Solar Label, "CAUTION - PV SYSTEM BACKFED", 4.125" X .75", Yellow
	Local Order Number 2	Cross Reference = 10 per pack: 596-00666; Metal Solar Placard 5 pack: 596-00834; Spanish version 50 per roll: 596-00827
	Short Description	Solar Label, 2017 Code, CAUTION PHOTOVOLTAIC SYSTEM BACKFED, 4.12" x .75", VL, Yellow, 50/roll
Product Dimensions	Length L (Imperial)	4.125"
	Length L (Metric)	104.6mm
	Width W (Imperial)	4.125"
	Width W (Metric)	104.6mm
	Height H (Imperial)	0.75"
	Height H (Metric)	19.05mm

596-00587



Material and Specifications		
	Material	Type 443/552, UV Stable Flexible White Vinyl with Acrylic Laminate
	Material Shortcut	443/552
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	Halogenfree	Yes
	Minimum Application Temperature	+50°F (+10 °C)
	Operating Temperature	-40°F to +174°F (-40°C to +79°C)
	ROHS Compliant	Yes
	Certification/Specification	NEC2011
UL Recognized (US)	Yes	
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055
	Labels per Column	1
	Labels per Row	1