

596-00630

HellermannTyton

Article Number: 596-00630

Description: Thermal Transfer Labels, Self-Laminating, 1.5" x .7" x 1.437", 1 Across, VL, White, 1000/roll



Base Data	
Local Order Number	596-00630
Type	TAG53T1-100B
Color	White (WH)
Features and Benefits	<ul style="list-style-type: none"> • HellermannTyton Self-Laminating Labels come on rolls on a standard 3" core for easy loading into a printer or caddy. • Labels are conformable so that they can bend around small gauge wires and tight bends without coming loose over time. • Labels are UL recognized for indoor and outdoor use to expand application options. • HellermannTyton thermal transfer labels work in any thermal transfer printer so that the use always has options to get labels printed without being locked into a single vendor.
Quantity Per	reel
Product Description	HellermannTyton thermal transfer self-laminating labels are a conformable vinyl film with a white printable surface followed by a clear tail that laminates the printed text when applied to a wire or cable. The labels are UL recognized for indoor and outdoor use with an aggressive acrylic adhesive that allows the label to bond to large and small diameter wires.
Short Description	Thermal Transfer Labels, Self-Laminating, 1.5" x .7" x 1.437", 1 Across, VL, White, 1000/roll
Product Dimensions	
Width W (Imperial)	1.5"
Width W (Metric)	37.65mm
Height H (Imperial)	0.7"
Height H (Metric)	17.78mm
Height H2 (Imperial)	1.43"
Height H2 (Metric)	36.5mm
Bundle Diameter Max. (Imperial)	0.29"
Horizontal Repeat HR (metric)	38.1mm
Horizontal Repeat HR (imperial)	1.5"
Print Method	Thermal transfer
Vertical Repeat VR (imperial)	1.62"

596-00630

HellermannTyton

Product Dimensions	Vertical Repeat VR (metric)	41.28mm
	Width of Liner WL (imperial)	1.6"
	Width of Liner WL (metric)	40.64mm
Material and Specifications	Material	Vinyl
	Material Shortcut	VL
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	Minimum Application Temperature	from +50°F (from +10°C)
	Operating Temperature	-40°F to +194°F (-40°C to +90°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3919102055
	Labels per Row	1