HellermannTyton



170-03146 Article Number:

Braided Sleeving, Split Wrap, Flame Retardant, 1.5" Dia, Black, 75 ft/bulk reel Description:

Base Data		
	Local Order Number	170-03146
	Туре	BSSWFR1120B
	Color	Black (BK)
	Features and Benefits	 Split wrap design installs quickly, saving assembly time and future accessibility without disassembly. Unique construction retains shape and rigidity throughout unrolling. Easy open design allows quick assembly, future access, and ability to apply protective sleeving post assembly or post installation situations.
	Quantity Per	box
	Product Description	A lateral split, semi-rigid and flame retardant braided sleeving configuration used when ease of installation and repeat access to wire bundle is required. The lateral split allows the sleeving to open and accommodate a variety of bundling requirements. The 25% edge overlap rolls back over connectors and splices without exposing the bundled wires.
	Short Description	Braided Sleeving, Split Wrap, Flame Retardant, 1.5" Dia, Black, 75 ft/bulk reel
Product Dimensions		
	Length L (Imperial)	75.0ft
	Length L (Metric)	22.9m
	Reel Length (imperial)	75.0ft
	Bundle Diameter Max. (Imperial)	1.5"
	Bundle Diameter Max. (Metric)	38.1mm
	Nominal Diameter (Imperial)	1-1/2"
	Nominal Diameter (Metric)	38.1mm
Material and Specifications		
	Material	Polyester (PET)
	Material Shortcut	PET
	Flammability	FAR 25
	Operating Temperature	-94°F to +248°F (-70°C to +125°C)
	·	

generated on: 4/28/2017

170-03146



Material and Specifications	ROHS Compliant	Yes
	UL Recognized (US and Canada)	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	75ft
	Package Quantity (Metric)	22.86m
	Customs Number(Schedule B)	3926909987
	Weight (imperial)	2.1lbs
	Weight (Metric)	0.95kg

generated on: 4/28/2017